

GOOSENECK TRAILERS

Gooseneck Trailers Models G-10, G-12, G-14, & G-16



The Pequea G Series trailers offer you more features than you expect to find. Designed to provide ease, safety, and convenience for the operator, this series has unique advantages whether you are hauling hay or construction equipment.

STANDARD FEATURES

- All welded "I" beam construction on G-14 & G-16 decks
- G-10 & G-12 have all welded structural "C" channel frames
- All models have tubular steel gooseneck
- Gussets welded at stress points
- Heavy duty slipper leaf springs
- Tandem heavy duty axles
- Large tires on industrial wheels
- DOT approved reflector tape
- Sealed, rubber mounted, plug in lights
- Modular factory wiring harness
- Unique lockable tool boxes
- Chain and utility storage racks

- "Step-up" with hand hold
- Electronically primed & painted
- Breakaway hitch
- Safety chains
- Heavy duty 12 K lbs. drop leg jack
- Well shielded, internally grounded, wiring
- 2" pressure treated decking
- Adjustable vertical ball hitch

OPTIONAL ADJUSTABLE BEAVER TAIL FEATURE

- Corrugated diamond plate Beaver Tail for easy & safe loading of equipment.
- Lift feature which extends usable flat deck surface by length of Beaver Tail



Ramps stowaway under bed on optional adjustable Beaver Tail.



Beaver Tail lifts and locks into place for full length flat bed.

GOOSENECK TRAILERS



Standard adjustable vertical hitch.



Convenient "hand-hold" and "step-up" are standard. Unique lockable tool boxes.



Chain utility mesh rack is standard.

GOOSENECK TRAILER SPECIFICATIONS

| Model | G-10 | G-12 | G-14 | G-16 |
|----------------------|----------------------------------|----------------|----------------|----------------|
| Length | 27' 9" | 27' 9" | 32' 9" | 32' 9" |
| Overall Width | 101" | | | |
| Deck Width | 96" | | | |
| Deck Hgt. w/bv. Tail | 20' | 20' | 25' | 25' |
| Beaver Tail | 4' | 4' | 5' | 5' |
| Deck Height | 2' 7 1/4" | 2' 9 1/4" | 2'-10" | 2' 11 1/4" |
| Hitch Height | 34" | 36" | 36" | 38" |
| Overall Height | 6' | 6' 2" | 6' 3" | 6' 4 1/2" |
| Axles (2) | 6000 ea. | 6000 ea. | 7000 ea. | 8000 ea. |
| Suspension | Slipper leaf springs | | | |
| Wheels | 6 bolt, 15" | 8 bolt, 16" | 8 bolt, 16" | 8 bolt, 17.5" |
| | white spoke | industrial | industrial | industrial |
| Tires | ST 225/75R | 245/75R | LT 235/85R | 215/75R |
| | 2540 load cap. | 3040 load cap. | 3750 load cap. | 4750 load cap. |
| Hitch | 2 5/16" vertical adjustable ball | | | |
| Jack cap. | 12,000 lbs. | | | |
| GVW rating | 10,000 lbs. | 12,000 lbs. | 14,000 lbs. | 16,000 lbs. |
| Trailer Weight | 3,200 lbs. | 3,350 lbs. | 4,500 lbs. | 4,750 lbs. |
| Brakes | Standard | | | |